

**FORK ARM**



STANDARD I.T.A

**HOOK CLASS II**

CLASS	CROSS SECTION	LENGTH		NET WEIGHT KG/PC	CAPACITY x LOAD CENTER KGxMM
		INCHES	MM		
II A (2A)	100x40 (4"x1.5")	42	1070	46	1000x500
		48	1220	51	
		54	1370	56	
		60	1520	61	
		72	1820	70	
II A (2A)	100x45 (4"x1.75")	42	1070	50	1250x500
		48	1220	56	
		54	1370	62	
		60	1520	67	
		72	1820	80	
II A (2A)	120x40 (5"x1.5")	42	1070	55	1250x500
		48	1220	62	
		54	1370	67	
		60	1520	74	
		72	1820	84	

**FORK ARM**

STANDARD I.T.A

**HOOK CLASS III**

CLASS	CROSS SECTION	LENGTH		NET WEIGHT KG/PC	CAPACITY x LOAD CENTER KGxMM
		INCHES	MM		
III A (3A)	125x45 (5"x1.75")	42	1070	67	1500x500
		48	1220	74	
		54	1370	81	
		60	1520	88	
		72	1820	100	
III A (3A)	125x50 (5"x2")	42	1070	75	2000x500
		48	1220	83	
		54	1370	90	
		60	1520	96	
		72	1820	108	
		96	2440	137	
III A (3A)	150x50 (6"x2")	42	1070	90	2250x500
		48	1220	101	
		54	1370	108	
		60	1520	118	
		72	1820	136	

MATERIAL:

CLASS II, III	MATERIAL	C%	Si%	Mn%	Cr%
FORK	<b>33MnCrTiB</b>	0.30-0.35	0.15-0.35	1.25-1.50	0.30-0.60

STANDARD I.T.A

**HOOK CLASS IV**

CLASS	CROSS SECTION	LENGTH		NET WEIGHT KG/PC	CAPACITY x LOAD CENTER KGxMM
		INCHES	MM		
IV A (4A)	150x65 (6"x2.5")	48	1220	142	3500x600
		54	1370	150	
		60	1520	162	
		72	1820	186	
		78	2440	235	

MATERIAL:

CLASS IV	MATERIAL	C%	Si%	Mn%	Cr%
FORK	<b>15B37</b>	0.30-0.35	0.15-0.35	1.25-1.50	0.30-0.60

**REMARKS:**

- 1, Mounting dimension conformed to ISO 2328
- 2, Only popular size listed above, please kindly check with us for other sizes.